



Profit industrial gloves are recommended for the installation of fire protection material. The gloves protect against mechanical risks and are manufactured in accordance to EN 388:2016.

Gloves		Test report		
	Palm	Result	Method	Unit
Abrasion resistance	Number of cycles to breakthrough - lowest value Performance level	> 8000 Level 4	EN 388: 2016	cycles
Puncture resistance	Force recorded - lowest value Performance level	45 Level 1	EN 388: 2016	N
Tear resistance	Total torn tearing force - lowest value Performance level	58 Level 2	EN 388: 2016	N
Blade cut resistance	I1	1,6	EN 388: 2016	Index
	I2	1,6		
	I3	1,7		
	I4	1,7		
	I5	1,6		
	I _{mean}	1,6		
	I1(2)	1,6		
	I2(2)	1,5		
	I3(3)	1,5		
	I4(4)	1,6		
	I5(5)	1,7		
	I _{mean} (2)	1,6		
	Performance level	Level 1		

Composition

The Profit gloves are made with 15 gauge, spandex and nylon knitted liners, coated with nitril and finished with a microfne foam.

Size

11

GENERAL INFO

- Installers should be trained or experienced to install and understand the product.
- Read and understand all technical datasheets and installation instructions before attempting to install, remove or adjust any Profit piping products.
- Depressurise and drain the sprinkler installation system before attempting to install, remove or adjust any Profit piping products.
- Never work on piping-systems that are pressurised and / or filled with water.
- These gloves must be stored properly, i.e. in dry condition. Influences such as humidity, temperature and light, as well as natural changes to materials over a period of time may result in a change of characteristics. An expiration time can not be specified, as this depends on the degree of wear and tear, utilization and the area of use.
- Profit reserves the right to change specifications, designs and/or standard equipment without notice and without incurring in any obligations.
- Use the necessary Personal Protection Equipment (PPE) to avoid personal injury (helmet, safety shoes and goggles, Profit gloves).



Failure to follow these instructions could result in death or serious injury and property damage.

We advise to always store our products in closed and dry environments, the products do not need any specific maintenance once installed on an aboveground sprinkler installation.